

DEVICE FOR A POLE SAW.

Device for a pole saw for pruning trees or bushes comprising an elongated stiff tube extending from a drive unit to a remote chain saw head and incorporating drive shaft connected to an input shaft of a gear arranged in the chain saw head the gear being provided with an output shaft on which a sprocket wheel for driving a saw chain is arranged.

Pole saws of the above type are previously known but rather often such saws start to vibrate heavily when being used. This is due to the fact that the teeth of the chain get stuck in the material being cut. When sufficient amount of energy then has been accumulated in the elastic transmission system the teeth might suddenly leave hold of the material thereby initiating said vibrations. The vibration level can be influenced by many different factors such as the gear ratio between the drive engine and the chain drive, the torque and bending stiffness of the guide bar, the drive shaft, the oscillating mass of the engine and saw head, the position of the chain bar guide, the rotation direction of the engine and so on. Mostly these factors are difficult to change without creating other disadvantages.

It has been suggested to solve the problem mentioned above by mounting a vibration damper at the outside of the sprocket wheel. A disadvantage with such an arrangement is however that the width of the saw head increases compared to a conventional arrangement. Moreover, because the damper is rather heavy the weight distribution becomes worse in particular since the weight of the guide bar and the chain are positioned at the same side of the saw head. A further disadvantage is that the damper is an obstacle when replacing the chain or when removing the guide bar.

The purpose of this invention is to create a simple and cheap vibration damper which is a part of an improved integrated weight distribution system and which is not an obstruction when replacing the chain or guide bar. The device according to the invention also reduces the width of the saw head and serves as a protection for the gear housing if the chain should come off the sprocket wheel. This is achieved by means of a device having the characteristics mentioned in the claims.

An embodiment of the invention will now be described with reference to the accompanying drawings on which Fig. 1 shows a pole saw in operating position, Fig. 2 is a perspective view of a saw head (without the guide bar and chain) which is a part of the pole saw whereas Fig. 3 is a horizontal section through the saw head in Fig. 2.

As appears from Fig. 1 the pole saw comprises a drive unit 10 such as an internal combustion engine or an electric motor that via an elongated stiff tube 11 is connected to a saw head 12 having a guide bar 13 on which an endless saw chain is arranged. The tube 11 encloses a drive shaft 14 that is driven by the drive unit 10 and is
5 connected to an inlet shaft 15 of a gear transmission 16 that is enclosed in a gear housing 17. The gear housing is an integrated part of the saw head and is preferably made of light metal. An outlet shaft 18 of the gear transmission is supported by a bearing 19 and has an outer end on which a sprocket wheel 20 is secured. The guide bar 13 is in the usual way clamped to the saw head by means of a bar bolt 21 which can be
10 loosened in order to make it possible to move the guide bar in its length direction in order to tighten the endless chain supported by the guide bar.

The sprocket wheel 20 has a hub part 22 on which a vibration damper 23 is secured and rotates together with the sprocket wheel. The vibration damper 23 is a circular, hollow, large mass body and is preferably made of steel or sintered material
15 but might as well be an integrated part of the sprocket wheel 20 or be supported by it. The vibration damper is placed at the inner side of the sprocket wheel 20 i.e. on the side that faces the gear housing and serves together with the hub part 22 that surrounds the bearing 19 as an outer protection for the gear housing 17 if the chain should get out of engagement with the sprocket wheel. The position of the vibration damper on said side
20 of the sprocket wheel also gives a far better weight distribution compared to an arrangement where the damper is placed on the other side of the sprocket wheel.

Claims

1. Device for a pole saw for pruning trees or bushes comprising an elongated stiff tube
5 (11) extending from a drive unit (10) to a remote chain saw head (12) and incorporating
a drive shaft (14) connected to an input shaft (15) of a gear (16) arranged in the chain
saw head (12) the gear being provided with an output shaft (18) on which a sprocket
wheel (20) for driving a saw chain is arranged **characterized in** that a mass body
vibration damper (23) is arranged between the gear (16) and the sprocket wheel (20).
- 10 2. Device for a pole saw according to claim 1 **characterized in** that the gear (16) is
enclosed in a gear housing (17) and that the damper (23) serves as an outer protection
for the gear housing.
3. Device for a pole saw according to claim 2 **characterized in** that the gear housing
(17) is an integrated part of the saw head (12).
- 15 4. Device for a pole saw according to claim 2 or 3 **characterized in** that the gear
housing (17) is made of light metal.
5. Device for a pole saw according to any of the previous claims **characterized in** that
the sprocket wheel (20) is provided with a hub part (22) surrounding a bearing (19) for
the output shaft (18).
- 20 6. Device for a pole saw according to any of the previous claims **characterized in** that
the damper (23) is an integrated part of the sprocket wheel (20) or is supported by it.

1

ABSTRACT

This invention relates to a device for a pole saw for pruning trees or bushes. The pole saw comprises an elongated stiff tube extending from a drive unit to a remote chain saw head (12) and incorporates a drive shaft (14) connected to an input shaft (15) of a gear (16) arranged in the chain saw head (12). The gear is provided with an output shaft (18) on which a sprocket wheel (20) for driving a saw chain is arranged. A mass body vibration damper (23) is arranged between the gear (16) and the sprocket wheel (20).

1/2



FIG. 1

2/2




FIG. 2




FIG. 3

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 2004/000468

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B27B 17/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B27B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI DATA, EPO-INTERNAL

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5718050 A (HAROLD A. KELLER ET AL), 17 February 1998 (17.02.1998), abstract, see the figures --	1-6
Y	US 200108045 A1 (JOHANNES MENZEL ET AL), 19 July 2001 (19.07.2001), figure 4, paragraph 21 --	1-6
A	US 4117594 A1 (JAMES A. ARBUCKLE), 3 October 1978 (03.10.1978), column 3, line 15 - column 4, line 9, figure 1 --	1-6
A	US 6182367 B1 (JERZY JANCZAK), 6 February 2001 (06.02.2001), see whole document --	1-6

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

27 April 2004

Date of mailing of the international search report

23 -06- 2004

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Kerstin Waczinska/MN
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

31/03/2004

International application No.
PCT/SE 2004/000468

US	5718050	A	17/02/1998	NONE		
US	200108045	A1	19/07/2001	NONE		
US	4117594	A1	03/10/1978	NONE		
US	6182367	B1	06/02/2001	AU	2192399 A	23/04/1999
				DE	19919385 A	02/12/1999
				JP	11346557 A	21/12/1999
				SE	509427 C	25/01/1999
				SE	9801708 A	25/01/1999